

Micro Signal Type Tester

II. TH1953/TH1963/TH1963A Digit Multimeter

Features

- 4.3-inch LCD color display, Chinese and English menu
- 6 1/2 bit 1199999 digits reading (TH1963/TH1963A)
- 5 1/2 digit 119999 digits reading (TH1953)
- Test speed up to 1000 / s
- Small size, front and rear input terminal, easy to shelve (TH1963 only)
- Histogram, bar graph, trend chart display
- AC low frequency signal can be tested down to 3Hz
- Capacitance test function
- Up to 5V diode test voltage
- Stores data up to 10,000
- Fast Chinese and English help



NEW

CE

RS232	LAN	USB HOST	USB DEVICE	GPIB OR HANDLER
standard	standard	standard	standard	option

Application

- Production line workbench
- Maintenance workbench
- Teaching laboratory
- Automated test equipment

TH1963

Rack mount (mm): 215(W) x 88(H) x 300(D)
Dimension (mm): 235(W) x 105(H) x 320(D)
Net weight: 2.7 kg

Specifications

Model	TH1963	TH1963A	TH1953					
Display	4.3-inch LCD color display							
Display digits	1199999 digits reading	119999 digits reading						
Measurement parameters								
DC voltage, AC voltage, DC current, AC current, DC resistance, capacitance, frequency, breakdown, diode, temperature								
Display mode	Direct reading, histogram, bar graph, trend chart							
Measurement speed	Up to 1000 times / s							
Math function	Reset function, Min / Max / Average / Standard deviation, dB, dBm							
Common features	Range	Trigger mode	Reading-hold	Limit measurement				
	Auto / Manual	LOCAL: AUTO / SINGLE / EXT REMOTE: IMMEDIATE / BUS / EXT	Yes	Hi, Lo and IN (PASS), with sound beep				
Technical Index	Uncertainty: \pm (% of reading +% of range), $T_{CAL}=25^{\circ}\text{C}$							
Parameters	Range / Test Range		Frequency	Highest annual accuracy $T_{CAL} \pm 5^{\circ}\text{C}$				
DC voltage	100.0000 mV - 1000.000V (TH1963/A) 100.000 mV - 1000.00V (TH1953)		TH1963	TH1963A	TH1953			
True RMS AC voltage	100.000mV - 750.000V		3 - 5Hz 5 - 10Hz 10Hz - 20kHz 20 - 50kHz 50 - 100kHz 100 - 300kHz	1.00 + 0.03 0.35 + 0.03 0.06 + 0.03 0.12 + 0.05 0.60 + 0.08 4.00 + 0.50	1.00 + 0.03 0.38 + 0.03 0.09 + 0.03 0.15 + 0.05 0.63 + 0.08 4.00 + 0.50			
DC Resistance	10Ω-100MΩ, Test current: 10mA - 500nA		100μA - 10mA 100mA 1A 3A 10A	0.010 + 0.001 0.050 + 0.006 0.050 + 0.004 0.100 + 0.004 0.200 + 0.020 0.120 + 0.010	0.014 + 0.001 0.050 + 0.005 0.050 + 0.004 0.100 + 0.004 0.200 + 0.020 0.120 + 0.010			
DC current	100μA - 100mA 1A 3A 10A		3kHz - 5kHz 5kHz - 10kHz 10kHz - 20kHz 20 - 50kHz 50 - 100kHz 100 - 300kHz	1.00 + 0.04 0.10 + 0.04 0.10 + 0.04 0.10 + 0.04 0.23 + 0.04 0.23 + 0.04	0.10 + 0.04 0.10 + 0.04 0.10 + 0.04 0.10 + 0.04 0.23 + 0.04 0.23 + 0.04			
AC current	100μA - 100mA 1A 3A 10A		3Hz - 5kHz 5kHz - 10kHz 10kHz - 20kHz 20 - 50kHz 50 - 100kHz 100 - 300kHz	0.23 + 0.04 0.23 + 0.04 0.15 + 0.04 0.15 + 0.04	0.23 + 0.04 0.23 + 0.04 0.15 + 0.04 0.15 + 0.04			
Frequency	3Hz - 10Hz 10Hz - 100Hz 100Hz - 1kHz 100Hz - 300kHz Square wave		3kHz - 5kHz 5kHz - 10kHz 10kHz - 20kHz 20 - 50kHz 50 - 100kHz 100 - 300kHz	0.100 0.030 0.010 0.010 0.010	0.100 0.030 0.012 0.012 0.012			
Diode	5V, Test current: 1mA		0.010 + 0.030	0.1 + 0.02				
Breakover	1kΩ, Test current: 1mA		0.010 + 0.030	0.1 + 0.02				
Capacitance	1.0000nF 10.000nF - 1.0000mF 10.000mF		1.0 + 0.5 0.5 + 0.1 1.0 + 0.5	0.02 0.02 0.02				
Temperature	PT100 (DIN/ IEC 751) 5 kΩ Thermistor		± 0.05°C ± 0.10°C					

Standard Accessories

3 cord power line

TH26017 USB Cable

TH26036 1 pair of test lead (red and black)